

Metal Alloy Low-Resistance Resistor

TYPE : LR2512 3W Series

SPECIFICATIONS

規 格 書

Issued by : _____ Date : _____

Checked by : _____ Date : _____

Approved by : 陳富強 Date : 2008/09/16

巨 馳 科 技 股 份 有 限 公 司


Giant Chip Technology Co., Ltd.

TEL : 886-2-8698-2189 FAX : 886-2-8698-2358

TEL : 886-7-301-0468 FAX : 886-7-301-0467

Metal Alloy Low-Resistance Resistor

Product Specification: LR2512 3W Type



FEATURES :

- ◆ Ideal for all types of current sensing, voltage division and Pulse applications including switching and linear power Supplies, Instruments, power amplifiers.
- ◆ Proprietary processing technique produces extremely low Resistance values.
- ◆ High-temperature performance (up to +275 °C)
- ◆ Very low inductance 0.5nH to 5nH
- ◆ Excellent frequency response
- ◆ Low thermal EMF (<1uV/°C)
- ◆ Lead(Pb)-free construction is RoHS-compliant

1. Standard Electrical Specifications :


Model	Power Rating at 100 °C (Watts)	Resistance Range m		
		0.5%(D)	1.0%(F)	5.0%(J)
LR2512-23	3.0	7~10	0.5~10	0.5~10

3 Watts with total solder pad trace size of 400mm²

2. Technical Specifications :

Parameter	Unit	LR2512-23 (m)
Temperature Coefficient	ppm /°C	0.5~2= +50 3~10 = -25
Operating Temperature Range	°C	-65 ~ +275
Maximum Working Voltage	V	(P × R) ^{1/2}

Ordering Information :



Packing

1=Tape & Reel ; B=Bulk Pack

1=1,000 Pcs

Tolerance

D=±0.5% ; F=±1.0% ; J=±5.0%

Resistance


EX : R001=1m ; R010=10m

Power Rating (Watts)

Number of Terminals

Model (Size)


3. Dimensions :



Model	DIMENSIONS - in inches (millimeters)				
	Resistance Range m	L	W	H	T
LR2512-23	0.5 ~ 1.5	0.246±0.010 (6.25±0.254)	0.13±0.010 (3.30±0.254)	0.031±0.010 (0.800±0.254)	0.074±0.010 (1.88±0.254)
	2~ 10	0.246±0.010 (6.25±0.254)	0.13±0.010 (3.30±0.254)	0.031±0.010 (0.80±0.254)	0.044±0.010 (1.13±0.254)
Model	SOLDER PAD DIMENSIONS - in inches (millimeters)				
	Resistance Range m	a	b	i	
LR2512-23	0.5 ~1.5	0.120(3.05)	0.145(3.68)	0.050(1.27)	
	2 ~ 10	0.083(2.11)	0.145(3.68)	0.125(3.18)	

Remark : 3 Watts with total solder pad trace size of 400mm²


4. Power Derating Curve :



5. Performance :


Test Item	Conditions of test	Test Method
Thermal Shock	- 55 °C to + 125 °C , 1000 cycles , 15 minutes at each extreme	JIS C5202 7.4
Solderability test	Steam aging:4 hrs, cool down 30 minutes then test	JIS C5202 6.5
Low Temperature Storage	-55°C for 1000 hours	JIS C5202 7.1
High Temperature Exposure	1000 hours @ + 155°C	JIS C5202 7.2
Bias Humidity	+ 85°C , 85% RH, 10% Bias, 1000 hours,90 minutes "ON" ,30 minutes "OFF"	JIS C5202 7.9
Mechanical Shock	100 grams for 6 milliseconds, 5 pulses	JIS C5202 6.13
Vibration	Frequency varied 55Hz in one minute , 3 directions , 12 hours	JIS C5202 6.7
Load Life	1000 hours @ rated power, + 100 °C , 1.5 hours "ON" , 0.5 hours "OFF"	JIS C5202 7.10
Resistance to Solder Heat	Solder temp./immersion time:260±5°C ,10±1secs and 350±10°C ,3.5±0.5secs	JIS C5202 6.4
Moisture Resistance	Mil-STD-202 , Method 106 , 0% power , 7a and 7b not required	JIS C5202 7.6
Resistance to solvent	Immersion time:60±5 secs,20 °C ~25 °C	JIS C5202 6.9

6. Marking :



7. Packaging :

Model	Reel			
	Tape Width	Diameter	Pieces/Reel	Code
LR2512-23	12mm/Embossed Plastic	178mm/7"	1,000	1



Unit: mm

Item	W	P1	E	F	Do	D1	P0	Po*10	P2	Ao	Bo	Ko	t
Spec.	12.00	8.00	1.75	5.50	1.50	1.50	4.00	40.00	2.00	3.90	6.74	1.08	0.24
Tole.	±0.10	±0.10	±0.10	±0.05	+ 0.10 - 0.00	±0.10	±0.05	±0.10	±0.05	±0.10	±0.10	±0.05	±0.05